

Input/Output Voltage	400Vac±10%	Output current	32A 3Phase
Input frequency	55±10%	Charging gun type	IEC 62196-2
Rated power	2*22KW	Cable length	4 meters
Power Factor	>0.99	Overall efficiency	0.96

**---Protection---**

Overvoltage protection	yes	Undervoltage protection	yes
Overload protection	yes	Short circuit protection	yes
Earth leakage protection	yes	Over temperature protection	yes
Lightning protection	yes	Overcurrent protection	yes

**---Function and Accessory---**

Network connection	Ethernet / 4G / No	Visual Indication	LED Indicator light
Communication Protocol	OCPP 1.6 / No	Push Button	Emergency Stop
LCD Display	4.3 inch screen	Language	English
RCD	Type A	RFID	yes

**---Working environment---**

Protection degree	IP55	Maximum altitude	Up to 2000m
Environment temperature	-20°C~+60°C	Cooling	Natural air cooling
Storage temperature	-40°C~+70°C	Operating humidity	≤95% non-comdensing
Applicable Scene	Indoor/Outdoor	Acoustic noise	< 55dB

# AC Level 2 EV Charger Station 22kW 32A Ocpp

## EV Charger Car Charging Pole

<b>Power</b>	7kW Dual Ports	22kW Dual Ports
<b>Input Voltage</b>	1-phase 230V ±20%	3-phase 400V ±20%
<b>Input Current</b>	32A	32A
<b>Internal RCD</b>	Dual Type-B RCCB	
<b>Meter</b>	Dual MID Certified Meter	
<b>Display</b>	7" LCD	
<b>Network Connectivity</b>	Ethernet / Wi-Fi / 4G	
<b>Communication Protocols</b>	Full OCPP1.6J, OCPP 2.0	
<b>Ingress Protection</b>	IP55	
<b>Operating Temperature</b>	-30°C to +50°C	
<b>Storage Temperature</b>	-40°C to +70°C	
<b>Certification</b>	CE, IEC 61851-1, IEC 62196-2	
<b>Packaging</b>	450 x 1530 x 320 mm	









